



US009636965B2

(12) **United States Patent**
Hirao

(10) **Patent No.:** **US 9,636,965 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **SUSPENSION SYSTEM**

(71) Applicant: **HITACHI AUTOMOTIVE SYSTEMS, LTD.**, Ibaraki (JP)

(72) Inventor: **Ryusuke Hirao**, Kamagaya (JP)

(73) Assignee: **HITACHI AUTOMOTIVE SYSTEMS, LTD.**, Ibaraki (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 174 days.

(21) Appl. No.: **14/487,151**

(22) Filed: **Sep. 16, 2014**

(65) **Prior Publication Data**

US 2015/0088379 A1 Mar. 26, 2015

(30) **Foreign Application Priority Data**

Sep. 20, 2013 (JP) 2013-195927

(51) **Int. Cl.**

B60G 17/00 (2006.01)

B60G 17/015 (2006.01)

B60G 17/016 (2006.01)

B60G 17/08 (2006.01)

(52) **U.S. Cl.**

CPC **B60G 17/015** (2013.01); **B60G 17/016** (2013.01); **B60G 17/08** (2013.01); **B60G 2202/24** (2013.01); **B60G 2202/25** (2013.01); **B60G 2400/102** (2013.01); **B60G 2400/104** (2013.01); **B60G 2400/106** (2013.01); **B60G 2400/252** (2013.01); **B60G 2400/50** (2013.01); **B60G 2400/64** (2013.01); **B60G 2500/104** (2013.01); **B60G 2800/012** (2013.01); **B60G 2800/014** (2013.01); **B60G 2800/162** (2013.01)

(58) **Field of Classification Search**

CPC combination set(s) only.

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,408,411 A * 4/1995 Nakamura B60G 17/0182

701/48

6,427,528 B1 * 8/2002 Yamakado G01M 17/0072

73/121

7,328,475 B2 * 2/2008 Smith F16L 55/28

134/8

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2011-173503 9/2011

Primary Examiner — Yonel Beaulieu

(74) *Attorney, Agent, or Firm* — Wenderoth, Lind & Ponack, L.L.P.

(57) **ABSTRACT**

A suspension system capable of improving maneuverability and stability, the suspension system including a force generation mechanism and a controller. The controller, which controls each of shock absorbers, includes a main control calculation unit, a longitudinal force reaction force calculation unit, a lateral force reaction force calculation unit, an addition unit, and a suspension reaction force consideration unit. The controller subtracts an output from a vertical force calculation unit including the longitudinal force reaction force calculation unit, the lateral force reaction force calculation unit, and the addition unit from an output from the main control calculation unit by the suspension reaction force consideration unit, thereby succeeding in calculating a vertical force applied between a vehicle body and each wheel as a value in consistency with an actual behavior of a vehicle.

10 Claims, 7 Drawing Sheets

